

EUKALIN D 4000 is a water based synthetic resin dispersion

Product description

EUKALIN D 4000 is a dispersion adhesive for windowing folding cartons.

Application

- window patching in folding boxes and special lamination applications
- do **not** use for side seam gluing of folding boxes

Product properties

- general purpose window glue that can be used for various film types; pre-treatment might be necessary depending on the film
- excellent lay-flat
- very clean machine run
- sufficient initial tack and high final bonding strength
- good cleaning properties
- odorless
- information regarding food law are available upon request

Technical specifications

Viscosity (Brookfield DVII+)	ca. 2.000 mPa*s ± 20 %
Color	white

Working instructions

Processing temperature	15 °C - 25 °C
Application by	roller / segment

Processing

Product is ready for use. Dilution with water possible. Cleaning with water.

Storage conditions

Stored in a cold and dry place (at 10-30°C) in the original container, the minimum shelf life is 6 months. Do not store below 0°C and protect from frost.

Regulations

Please refer to the safety data sheet for detailed information on:

- hazardous goods labeling
- transport regulations
- safety regulations

This information is based on the present state of our knowledge and does not imply any acceptance of liability for loss, damage or consequential loss arising directly or indirectly from the use of the information or the use of the Company's products described herein. No warranty is given or implied that use of the information or any such product does not infringe the proprietary rights of any third party. Users are solely responsible for any use made of the product and should therefore satisfy themselves by appropriate trials that the product to be used is suitable for the intended use and that such use will not infringe any proprietary rights of any third party.