

EUKALIN 615 VB is a blend of resins, oil, waxes and a polymer

Product description

White polyolefin-based hotmelt adhesive

Application

Suitable for a wide range of applications in paper and board converting:

- bonding of paper & cardboard also printed & lacquered
- carton closing
- production of trays
- covering cartons
- folding boxes

Product properties

- high adhesion
- clean machine running
- high thermostability (processing)
- low tailng (angel hair)
- high bonding strength in the range 35°C to +60°C (depending on substrate and design or geometry; own tests are necessary)
- low odour

Technical specifications

Viscosity (Brookfield DVII+) 160°C	ca. 1.300 mPa*s ± 25 %
Color	white
Softening point	100 - 110 °C
Open time	long
Setting time	long

Working instructions

Working temperature	150 °C - 170 °C
Application by	disc / nozzle


Storage conditions

Stored in a cold and dry place in the original container, the minimum shelf life is 24 months.

Regulations

Please refer to the safety data sheet for detailed information on:

- hazardous goods labeling
- transport regulations
- safety regulations



This information is based on the present state of our knowledge and does not imply any acceptance of liability for loss, damage or consequential loss arising directly or indirectly from the use of the information or the use of the Company's products described herein. No warranty is given or implied that use of the information or any such product does not infringe the proprietary rights of any third party. Users are solely responsible for any use made of the product and should therefore satisfy themselves by appropriate trials that the product to be used is suitable for the intended use and that such use will not infringe any proprietary rights of any third party.