

TECHNICAL INFORMATION

- SPECIAL FEATURES**
- ✓ Excellent dimensional stability for larger wood boards
 - ✓ Very high shear strength
 - ✓ Regulates residual moisture
 - ✓ Extremely easy to spread
 - ✓ Excellent ridges
 - ✓ Hard adhesive (ISO 17178)

- SUITABLE SUBFLOORS**
- ✓ Sanded mastic asphalt
 - ✓ Concrete C25/30 DIN 1045
 - ✓ Calcium sulphate (floating) screed
 - ✓ Wood subfloors
 - ✓ STAUF fillers
 - ✓ Chipboards V100 (E1), OSB boards
 - ✓ Cement screed

- COLOUR**
- ✓ Light brown

REQUIRED QUANTITIES PER M²

- ✓ Approx. 1,000-1,500 g

OPEN TIME

- ✓ Approx. 20 min. at 20 °C

ACCESSIBILITY

- ✓ After 24 hours

SHELF LIFE

- ✓ 12 months

AVAILABLE PACKAGING

- ✓ 8 kg plastic bucket
- ✓ 18 kg plastic bucket

EMICODE

- ✓ EC 1 R^{PLUS}

GISCODE

- ✓ RS 10 solvent free

DIBT APPROVAL NO.

- ✓ Z-155.10-59



STAUF
seit 1828

CONTACT US TODAY

- ☎ +49 2739 301-0
- 📠 +49 2739 301-200
- ✉ info@stauf.de
- 🌐 www.stauf.de

STAUF
seit 1828

SPU 570

The safest way of bonding parquet



STAUF KLEBSTOFFWERK GMBH

Oberhausener Str. 1 . 57234 Wilnsdorf . Germany

12.2017/V2/250/RD

SUPERIOR STRENGTH

FUNCTIONALLY STABLE The STAUF SPU 570 has similar strength values as a 2-component PU adhesive. It is especially good at keeping large wooden floors (10:1 and wider) in shape. It is now suitable for bonds which were previously only feasible using shear-resistant 1-component and 2-component PU adhesives. However the STAUF SPU 570 can also be used uncompromisingly for all other solid or multilayer types of parquet flooring.

The right degree of elasticity ensures an absolutely solid bond with the subfloor, even where changes occur to the room climate. Moreover the STAUF SPU 570 has no adverse interaction with any STAUF parquet sealants/varnishes, mastic asphalt or existing subfloors.

NO CHANCE FOR RESIDUAL MOISTURE

ASSURANCE To attain the moisture-retarding barrier effect of the adhesive, apply several coats using notched trowel no. 12.

ABSOLUTELY HARMLESS

WITHOUT ANY PLASTICIZING INGREDIENTS

The STAUF SPU 570 solvent-free adhesive for parquet flooring is not subject to mandatory labelling nor does it contain any sensitising substances. It makes a valuable contribution to workplace hygiene and reduction of emissions.



Protection against damage caused by residual moisture

Direct bonding to cement screeds with up to 4 CM% and concrete subfloors with up to 6 % residual moisture by weight

Moisture barrier when applied in multiple coats



Solvent free –
GISCODE RS 10
Very low emissions

Not subject to
toxic classification

Without any
plasticizing ingredients

Isocyanate-free –
particularly user-friendly



STAUF ACCESSORIES

Notched trowel no.
3, 4, 5, 12, 14